

a pair of bead portions each provided therein with a bead core made of windings of at least one wire,

a carcass ply of cords extending between the bead portions and turned up around the bead core from the axially inside to the outside of the tire to form a pair of turnup portions and a main portion therebetween,

a rubber bead apex disposed radially outside the bead core and between each said turnup portion and the main portion,

a fiber reinforced rubber spacer interposed between the bead core and the carcass ply to provide a positive distance between the carcass ply cords and bead core wire,

said fiber reinforced rubber spacer having a securing portion which extends radially outwardly and axially outwardly from the axially inside of the bead core while separating from the bead core but contacting with the rubber bead apex, and

a distance (L1, L2) between an outermost point of said securing portion and the bead core being in a range of from 0.05 to 1.0 times a height of the bead core, wherein

said fiber reinforced rubber spacer is made of a single rubber strip reinforced with organic fibers,

said single rubber strip is loosely wound at least once around the bead core to form a slack portion radially outside the bead

Q1
sub B17
core, and said securing portion is formed by the slack portion,
a rubber layer inserted between the slack portion and a
radially outer face of the bead core is harder than the rubber bead
apex.

6. (amended) A pneumatic tire comprising

A2
a pair of bead portions each provided therein with a bead core
made of windings of at least one wire,

a carcass ply of cords extending between the bead portions the
outside of the tire to form a pair of turnup portions and a main
portion therebetween,

a rubber bead apex disposed radially outside the bead core and
between each said turnup portion and the main portion,

a fiber reinforced rubber spacer interposed between the bead
core and the carcass ply to provide a positive distance between the
carcass ply cords and bead core wire,

said fiber reinforced rubber spacer having a securing portion
which extends radially outwardly and axially outwardly from the
axially inside of the bead core while separating from the bead core
but contacting with the rubber bead apex, and

Q2 a distance (L1, L2) between an outermost point of said securing portion and the bead core being in a range of from 0.05 to 1.0 time a height of the bead core,

said fiber reinforced rubber spacer being made of a single rubber strip reinforced with organic fibers,

said single rubber strip loosely wound at least once around the bead core to form a slack portion radially outside the bead core, and said securing portion formed by the slack portion, wherein

said single rubber strip is wound, starting from a position under the bead core, towards the axially inside of the tire, and after wound one or more times it is continuously wound toward the radially outside, but from a certain point, it separate from the previous winding and extends radially outwardly along the carcass ply main portion while contacting with an axially inside of the rubber bead apex, so that a distance between a radially outer end of this radially outwardly extending portion and the bead core is in a range of from 0.05 to 1.0 times the height of the bead core.

7. (amended) A pneumatic tire comprising

Q2 a pair of bead portions each provided therein with a bead core made of windings of at least one wire,

a carcass ply of cords extending between the bead portions and turned up around the bead core from the axially inside to the outside of the tire to form a pair of turnup portions and a main portion therebetween,

a rubber bead apex disposed radially outside the bead core and between each said turnup portion and the main portion,

a fiber reinforced rubber spacer interposed between the carcass ply cords and bead core wire,

said fiber reinforced rubber spacer having a securing portion which extends radially outwardly and axially outwardly from the axially inside of the bead core while separating from the bead core but contacting with the rubber bead apex, and

a distance (L1, L2) between an outmost point of said securing portion and the bead core being in a range of from 0.05 to 1.0 times a height of the bead core, wherein

said fiber reinforced rubber spacer is made of a single rubber strip reinforced with organic fibers,

said single rubber strip is wound, starting from a position under the bead core, towards the axially inside of the tire, and